

Canon

CanoScan D660U

USB Flatbed Scanner

CanoScan[®] D660U

- Built-in 35mm film adapter for negatives and slides
- 600 x 1200 dpi for prints
- 35mm film scanning at 1200 x 1200 dpi
- 42-bit for over 4 trillion possible colors
- USB connection to Mac[®] and PC

Photo And Film Scanning Made Easy.

Film and photo scanning has become a true pleasure. No adapter hassles. No add-on kits. Everything you need to create high-quality scans is built into the CanoScan D660U USB Flatbed Scanner. And all of it is available with the push of a scan button.

High-quality and convenience come standard.

Lift the cover, insert your slide or negative and press the external film scan button. The D660U scanner, with its built-in backlight, produces spectacular 1200 x 1200 dpi film scans using VAROS™ technology. In fact, it features a remarkable 42-bit resolution, making more than four trillion possible colors available for richer, more robust images. Press the second external scan button for convenient photo-print or document scanning at an impressive 600 x 1200 dpi—high-quality for Web sites, graphic-design projects, duplicating or archiving photos, or simply scanning text for integration into word-processing documents.

Easy start-up, right out of the box.

The only thing easier than using the D660U scanner is setting it up. A simple USB cable plugs into any compatible Mac or PC. Load the software—complete with step-by-step instructions—and you're ready to go. Plus, the included free software suite features numerous easy tools to help you create great-looking projects, enhance and manipulate photos, or integrate scanned text.



Technical Information

Scanner Type	Flatbed, color and monochrome
Scanning Element	Charged Couple Device (CCD)
Light Source	Cold Cathode Lamp
Optical Resolution	Print: 600 x 1200 dpi Film: 1200 x 1200 dpi using VAROS™ technology
Maximum Resolution	9600 x 9600 dpi
Scanning Mode	Color: 42-bit internal/24-bit external Grayscale: 14-bit internal/8-bit external Black & White Text enhanced
Document Size	Print: up to 8.5" x 11.7" max. Film: 35mm film
Interface	USB
Dimensions (W x L x H)	10.2" x 17.3" x 3.9"
Weight	5.7 lbs.
Cable Length	Approx. 5 ft.
Common System Requirements	32MB RAM (64MB recommended); Color monitor with 800 x 600 or higher display and 16-bit color or more; CD-ROM drive (2x or faster); USB port (excludes add-on board)
Windows® System Requirements	Windows 98, Windows 2000 Professional; Pentium® 133Mhz processor or higher
Macintosh® System Requirements	Mac® OS (8.5 or later); iBook™, iMac™ G3 or G4 processor
Compatibility	Canon Plug-in Module CS-U for Mac OS (8.5 or later); ScanGear® CS-U TWAIN for Windows 98 and Windows 2000 Professional
Software	Software CD-ROM, including: ScanGear CS-U TWAIN driver, ScanGear Toolbox CS, Canon Plug-in Module CS-U, CanoScan Toolbox CS, ArcSoft® PhotoStudio® 2000, ArcSoft PhotoBase™ and ScanSoft® OmniPage® OCR
Power Requirements	120V AC, 60Hz
Maximum Power Consumption	15W (5W standby)
Environmental Conditions (without condensation)	Operating temperature: 41°–95°F Storage temperature: -40°–140°F Operating humidity: 15%–85% RH Storage humidity: 10%–90% RH
Warranty	1-year limited warranty

† Conditions and restrictions apply. See Extended Service Plan agreement for details.

Ordering Information

Description	Order #
Scanner CanoScan D660U	F91-4831-US1
Canon Extended Service Plan† 2-year extension with InstantExchange	CST-6286-000

For More Information Visit

www.canoscan.com
www.ccsi.canon.com
www.canonprintplanet.com

For a name of a dealer nearest you, call:
1-800-OK-CANON

Canon Computer Systems, Inc.
2995 Redhill Avenue, Costa Mesa, California 92626
1-714-438-3000

Canon Canada, Inc.
6390 Dixie Road, Mississauga, Ontario L5T 1P7, Canada
1-800-OK-CANON

Canon Latin America, Inc.
6505 Blue Lagoon Drive, Suite 325, Miami, Florida 33126
1-305-260-7400